

ZESTAWIENIE STALI DO RYS. 10K				Dł. całkow. [m]			
Nr	Średnica	Dł. 1 szt. L [m]	Il. szt.	S3SXB φ 8	# 10	RB400W # 12	# 16
Podciąg 2.1.			1 szt.				
1	# 16	4,100	4	-	-	-	16,40
2	# 12	3,830	2	-	-	7,66	-
3	# 16	3,760	7	-	-	-	26,32
4	# 12	4,000	2	-	-	8,00	-
5	# 16	6,320	7	-	-	-	44,24
6	# 12	4,950	2	-	-	9,90	-
7	# 16	1,520	2	-	-	-	3,04
8	# 16	2,900	2	-	-	-	5,80
9	# 16	6,660	4	-	-	-	26,64
10	# 16	6,440	4	-	-	-	25,76
11	# 12	4,270	2	-	-	8,54	-
12	# 16	6,820	7	-	-	-	47,74
13	φ 8	1,560	150	234,00	-	-	
Podciąg 2.3.			1 szt.				
14	# 16	6,680	5	-	-	-	33,40
15	φ 8	1,460	28	40,88	-	-	
16	# 12	7,600	2	-	-	15,20	-
Podciąg 2.4.			1 szt.				
17	# 16	3,980	4	-	-	-	15,92
18	# 12	4,550	2	-	-	9,10	-
19	φ 8	3,500	2	7,00	-	-	
20	φ 8	1,220	50	61,00	-	-	
Dł. og. [m]				342,88	0,00	58,40	245,26
Masa jedn. [kg/m]				0,395	0,617	0,888	1,580
Masa wg średnic [kg]				135,44	0,00	51,86	387,51
Masa wg gatunków [kg]				135,4		439,4	

ZESTAWIENIE STALI DO RYS. 11K					Dł. całkow. [m]		
Nr	Średnica	Dł. 1 szt. L [m]	Il. szt.	S3SXB φ 8	# 10	# 12	# 16
Podciąg 2.8.				2 szt.			
1	# 12	5,780	24	-	-	138,72	-
2	φ 8	5,080	24	121,92	-	-	-
3	# 16	5,280	48	-	-	-	253,44
4	# 16	1,600	56	-	-	-	89,60
5	φ 8	1,390	600	834,00	-	-	-
6	# 12	3,300	4	-	-	13,20	-
7	# 12	2,800	4	-	-	11,20	-
8	φ 8	1,580	46	72,68	-	-	-
9	# 12	4,740	4	-	-	18,96	-
10	# 12	2,120	4	-	-	8,48	-
11	# 10	2,600	8	-	20,80	-	-
12	# 10	1,240	8	-	9,92	-	-
Podciąg 2.7.				1 szt.			
14	# 16	5,550	2	-	-	-	11,10
15	φ 8	4,700	2	9,40	-	-	-
16	# 16	6,230	6	-	-	-	37,38
17	# 16	4,400	2	-	-	-	8,80
18	# 16	3,300	2	-	-	-	6,60
19	# 16	4,470	2	-	-	-	8,94
20	φ 8	4,500	2	9,00	-	-	-
21	φ 8	1,600	82	131,20	-	-	-
22	φ 8	6,000	2	12,00	-	-	-
Nadproże 2.9				3 szt.			
23	# 12	4,000	6	-	-	24,00	-
24	# 12	3,500	6	-	-	21,00	-
25	φ 8	1,460	48	70,08	-	-	-
Dł. og. [m]					1260,28	30,72	235,56
Masa jedn. [kg/m]					0,395	0,617	0,888
Masa wg średnic [kg]					497,81	18,95	209,18
Masa wg gatunków [kg]					497,8		885,2
ZESTAWIENIE TRZPIENI DYLAACYJNYCH							
Nr	Typ	Producent	Il. szt.				
3	CRET 124	Halfen	2				

ZESTAWIENIE STALI DO RYS. 13K				Dł. całkow. [m]				
Nr	Średnica	Dł. 1 szt.		S3SXB	RB400W			
		L [m]	Il. szt.		φ 8	# 10	# 12	# 16
Podciąg 2.11								
1	# 16	6,000	3	-	-	-	-	18,00
2	# 12	6,000	10	-	-	60,00	-	-
3	# 12	1,360	8	-	-	10,88	-	-
4	# 10	1,340	3	-	4,02	-	-	-
5	φ 8	2,580	52	134,16	-	-	-	-
Dł. og. [m]				134,16	4,02	70,88	18,00	
Masa jedn. [kg/m]				0,395	0,617	0,888	1,580	
Masa wg średnic [kg]				52,99	2,48	62,94	28,44	
Masa wg gatunków [kg]				53,0		93,9		